

SEWOO MOBILE PRINTER

LK-P24, LK-P34


SEWOO AMC Solution!

Advanced Manual Cutter

The AMC solution is a new cutting technology that is used in mobile printers for easy handling of paper cut by pushing a button with one hand.



Reliable Cutter by SEWOO
AMC(Advanced Manual Cutter) Technology



Key Features

- Receipt Mobile Printer
- Prints at 100mm per second
- Strong and Powerful Design against Dust and Water (LK-P24 : IP43, LK-P34 : IP54)
- Long battery life (LK-P24 : 1,510mAh, LK-P34 : 2,000mAh)
- Easy Bluetooth connection setting by using NFC function!
- Light Weight



2-inch
LK-P24



3-inch
LK-P34



MODEL		LK-P24	LK-P34
PRINTING	METHOD	Direct Thermal	
	SPEED	Max. 100mm / sec.	
RESOLUTION		203 DPI	
PAPER	PAPER TYPE	Thermal Receipt	
	WIDTH	Max. 58mm	Max. 80mm
	THICKNESS	0.06-0.09mm	
	ROLL MAX DIAMETER	40mm	50mm
	ROLL CORE	12.5mm	
CHARACTER		Font A(12×24), Font B(9×17), Asian Font(KOR,JPN,CHN-GB2312,CHN-Big5), Font0/1/2/4/5/6/7, Resident TTF, Downloadable TTF, FontA~H, FontGS, Resident TTF(Font0), Font 1~8	
BARCODE	1D	EAN-8,EAN8(+2+5), EAN-13, EAN13(+2+5), Codabar, Code11, Code39, Code93, Code128, ITF, LUPCA(+2+5), UPC-E, UPC-E(+2+5), Planet, UPC-A etc	
	2D	PDF417, QR, Maxicode, RSS14, TLC39, Datamatrix, Aztec, MicroPDF417	
EMULATION		ESC/POS, CPCL, ZPL Command compatible	
DRIVER		Windows Driver(10, 2012, 8, 7, 2008, VISTA, 2003, XP, 32bit & 64bit), Window CE & Mobile Driver & SDK(CE4.2~, Mobile 5.0~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, iOS SDK, Android(2.1~) SDK, Blackberry SDK, Symbian	
SENSOR		Black mark, Cover open, Paper end	
RELIABILITY	TPH	50km	
	PULSE ACTIVATION	50,000,000 pulse or more(12.5% Print Ratio)	
INTERFACE	STANDARD	USB	
	OPTION	Wi-Fi(802.11a/b/g/n), Bluetooth Smart Ready(Bluetooth 4.2+BLE), NFC TAG	
BATTERY CHARGER	INPUT	AC100~240V, 50/60Hz	
	OUTPUT	8.4V , 800~1400mA	
BATTERY	BATTERY TYPE	Li-ion	
	OUTPUT	7.4V, 1510mAh	7.4V, 2000mAh
	CHARGING TIME	2.5Hrs (55Hrs stand-by)	3Hrs (77Hrs stand-by)
CUTTER		AMC(Advanced Manual Cutter)	
SIZE [W x D x H (mm)]		81.5×121.4×45.3	107.5×145×56
IP		IP43	IP54
Weight		261.5g (with Battery)	415.3g (with Battery)
TEMPERATURE	OPERATION	-10~50 °C	
	STORAGE	-20~60 °C	
HUMIDITY	OPERATION	10 ~ 80%	
	STORAGE	10 ~ 90%	

*All specification and desings are subject to change without notice.