

STYLISH AND INNOVATIVE
4 INCH RECEIPT / LABEL PORTABLE PRINTER

MOBILE PRINTER

LK-P41

- High gloss cover and 2 color LEDs
- IP42, IP54(with optional case) certified : protection against dust and water
- Adjustable paper width from 50mm to 112mm
- 2 types of battery selectable – 2600/5200mAh Li-ion
- Large capacity, paper rolls up to 56mm (OD)
- Highly reliable Bluetooth communications or Wi-Fi(802.11 a/b/g/n) available(option)
- ESC/POS, CPCL command compatible
- Various O/S drivers : Win CE/Mobile, Symbian, Linux, Blackberry, Android



Made for
iPod iPhone iPad



COVER OPEN



ACCESSORIES



CASE


CRADLE

STRAP

SPECIFICATION

ITEM	TYPE	
MODEL	LK-P41	
PRINTING	METHOD	Direct Thermal
	SPEED	80mm / sec
DOT DENSITY	203 DPI	
DOT PITCH	8dots /mm, 0.125 pitch	
EFFECTIVE PRINTING WIDTH	104mm, 832dots/line	
PAPER	TYPE	Thermal Paper / Label
	WIDTH	50mm ~ 112mm
	THICKNESS	0.06mm ~ 0.16mm
	ROLL DIAMETER	Max. ø 56.0mm
RELIABILITY	ROLL CORE INNER	12.5mm ± 0.5mm
	TPH LIFE	50km
FONTS and GRAPHICS	IP	IP54(with case) certified
	STANDARD FONTS	Seven resident fonts 12-48 pt.
	OPTIONAL GRAPHICS, LINE AND BOX DRAWING	International character sets PCX and Bitmap
BARCODE	EAN-8, EAN-13, Code 39, ITF, UPC-A, UPC-E, Codabar, Code 93, Code 128, PDF 417(2D), QR Code(2D), Maxicode(2D)	
EMULATION	ESC/POS, CPCL Command compatible	
DRIVER	Windows Driver(10, 2012, 8, 7, 2008, VISTA, 2003, XP, 32bit & 64bit), Window CE & Mobile Driver & SDK(CE 4.2~, Mobile 5.0~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, iOS SDK, Android(2.1~) SDK, Blackberry SDK, Symbian	
SENSOR	Paper end / Black mark / Gap / Cover open sensors	
INTERFACE	STANDARD	Serial(RS-232C), USB
	OPTION	Bluetooth class 2, Wi-Fi(802.11 a/b/g/n)
BATTERY CHARGER	External Charger (Output 8.4VDC/0.8A)	
BATTERY	7.4V 2600mAh, 5200mAh	
	3.3Hrs Charging time(2600mAh)	
	6.2Hrs Charging time(5200mAh)	
	165Hrs Stand-by(5200mAh)	
DIMENSION	149mm x 162mm x 70mm (W x D x H)	
WEIGHT	572g (With 2200mAh Battery)	
TEMPERATURE	OPERATION	-10 ~ 50°C
	STORAGE	-20 ~ 60°C
HUMIDITY	OPERATION	35 ~ 80%
	STORAGE	10 ~ 90%

● All specification and desings are subject to change without notice.



J. STEPHEN Co., Ltd.

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do,
18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-459-8880

www.miniprinter.com